OLI 1 9 2005 W

#AF ZIW

PTO/SB/2/09-04)
Approved for use through 07/31/2006. OMB/0651-0031
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no bers	Application Number	lection of information unless it displays a valid OMB control number.			
TRANSMITTAL	Filing Date	11/18/2003			
FORM	First Named Inventor	Mark N. Heflin			
	Art Unit	3644			
(to be used for all correspondence after initial filing)	Examiner Name	Dinh, Tien Quang			
Total Number of Pages in This Submission 15	Attorney Docket Number	991316			

100	at Number of	ragesiii	Inis Submission	12		 9913	10		
ENCLOSURES (Check all that apply)									
	Fee Transmittal Form Fee Attached Amendment/Reply After Final Affidavits/declaration(s) Extension of Time Request Express Abandonment Request Information Disclosure Statement Certified Copy of Priority Document(s) Reply to Missing Parts/ Incomplete Application Reply to Missing Parts under 37 CFR 1.52 or 1.53		Drawing(s) Licensing-related Papers Petition Petition to Convert to a Provisional Application Power of Attorney, Revocation Change of Correspondence Address Terminal Disclaimer Request for Refund CD, Number of CD(s) Landscape Table on CD Remarks		After Allowance Communication to TC Appeal Communication to Board of Appeals and Interferences Appeal Communication to TC (Appeal Notice, Brief, Reply Brief) Proprietary Information Status Letter Other Enclosure(s) (please Identify below):				
SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT									
Firm Na Signate Printed	ıre	Ala	ted States Word P in P. Klein	Army Lle	1				
		10,	/1·1/2005			 . tog. 110.	2	6 , 926	
CERTIFICATE OF TRANSMISSION/MAILING									
I hereby certify that this correspondence is being facsimile transmitted to the USPTO or deposited with the United States Postal Service with sufficient postage as first class mail in an envelope addressed to: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450 on the date shown below: Signature									
Typed or printed name Diane R. Winter Date 10/11/2005									

This collection of information is required by 37 CFR 1.5. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to 2 hours to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

TRANSMITTAL OF APPEAL BRIEF

In re Application of: Mark N. Heflin, et al.

Application No.

Filing Date

Examiner

Group Art Unit

Confirmation No. 4994

Docket No. 991316

10/715,243

11/18/2003 Dinh, Tien Quang 3644

Invention: Non-Pyrotechnic Remote-Controlled Parachute Jettison Device

TO THE COMMISSIONER OF PATENTS:

Transmitted herewith in triplicate is the Appeal Appeal filed: Aug 31, 2005	Brief in this application, with respect to the Notice of
The fee for filing this Appeal Brief is <u>\$500.0</u>	0
X Large EntitySmall En	ntity
A petition for extension of time is also enclor. The fee for the extension of time is	sed.
A check in the amount of	is enclosed
X Charge the amount of the fee to Deposit Acc	ount No. 50-1340
Payment by credit card. Form PTO-2038 is a	attached
<u>X</u> The Director is hereby authorized to charge a overpayment to Deposit Account No. 15-134 This sheet is submitted in duplicate.	any additional fees that may be required or credit any
Alen P Clein	Dated: 10/11/2005
Alan P. Klein Attorney, Reg. No.: 26,926	

UNITED STATES ARMY LEGAL SERVICES AGENCY

901 North Stuart Street, Suite 527

Arlington, VA 22203-1837

(703) 696-8113





IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application: MARK N. HEFLIN JAMES B. STEWART SAMUEL L. KAESEMEYER Serial No. 10/715,243

Filed: 11/18/2003

For: NON-PYROTECHNIC REMOTE-CONTROLLED PARACHUTE JETTISON DEVICE Art Unit No. 3644
Examiner: Dinh, Tien Quang
Confirmation No. 4994

APPEAL BRIEF

Commissioner for Patents P.O. Box 1450 Alexandria, VA 22313-1450

Sir:

On August 31, 2005, Appellants appealed to the Board of Patent Appeals and Interferences from the last decision of the Examiner. What follows is Appellants' brief as required by 37 CFR 1.192(a).

1. Status of Claims

Claims 2-5, 14 and 15 are allowed. Claims 16-20 were withdrawn. Claims 1 and 6-13 are on appeal.

2. Status of Amendments

10/17/2005 MBIZUNES 00000003 501340 10715243 01 FC:1402 500.00 DA The amendment filed after final rejection amending claim 2 was entered by the Examiner.

3. Summary of the Invention

The invention is directed to a device for severing an extraction line (see page 3, lines 9-11, of the specification, and reference numeral 25 of FIG. 1) connected between a cargo load (see page 3, lines 9-11, of the specification, and reference numeral 17 of FIG. 1) and an extraction parachute (see page 3, lines 9-11, of the specification, and reference numeral 21 of FIG. 1) when the cargo load fails to eject from an aircraft.

The device comprises a cutter (see page 3, lines 14-15, of the specification, and reference numeral 27 of FIGS. 2-4) spaced from and spring-biased in the direction of the extraction line, and a housing (see page 3, line 15, and page 4, lines 1-8, of the specification, and reference numerals 39-69 of FIGS. 2-4) for the cutter. In addition, the device includes means for mechanically restricting the cutter from engaging and severing the extraction line (see page 3, lines 15-16, and 18-20, of the specification, and reference numeral 31 of FIGS. 2-3), and means responsive to a radio signal from a transmitter on the aircraft for disabling the restricting means so that the cutter is released and severs the extraction line (see page 3, lines 17-18, and 20-23, of the specification, and reference numerals 33-37 of FIGS. 2-4).

Dependent claims 6-13 further define the housing of the device.

4. Issue

Whether the rejection of claims 1 and 6-13 under 35 U.S.C. § 103(a) as obvious over <u>Underwood</u> (U.S. Pat. 5,816,535) in view of <u>Kenzie</u> (U.S. Pat. 4,513,931) and <u>Tillman</u> (U.S. Patent 6,578,885) is proper.

5. Arguments

The primary reference, <u>Underwood</u>, discloses a system for releasing a cargo extraction parachute if the cargo attached to the parachute becomes jammed within the cargo compartment. (Col.1, lines 6-9.) Referring to FIG. 1, the extraction parachute 32A includes an attachment line 34A that is releasably connected to an extraction force transfer coupling 36A. (Col.4, lines 29-32.) Referring to FIG. 2, the end of the attachment line 34A is in the form of a loop 44 that is wrapped about a pin 38. (Col.4, lines 39-41.) An electrically initiated explosively actuated line cutter 62 is mounted on the coupling 36A positioned such that, when actuated, its cutter 64 severs the looped end of the attachment line 28 freeing the extraction parachute 32A. (Col. 4, lines 55-58.)

The primary reference, taken alone, does not teach the invention recited in the claims. Respecting base claim 1, for example, <u>Underwood</u> does not teach either a

spring-biased line cutter, or means for mechanically restricting a spring-biased line cutter from engaging and severing the extraction line, or means responsive to a radio signal from a transmitter on the aircraft for disabling the restricting means so that the cutter is released and severs the extraction line.

It is the Examiner's position that <u>Kenzie</u> shows a spring-biased line cutter, means for mechanically restricting a spring-biased line cutter from engaging and severing a line, and means for disabling the restricting means so that the cutter is released and severs the line, and that it would have been obvious to substitute the same for the electrically initiated-explosively actuated line cutter in <u>Underwood</u>'s combination of an extraction line and an electrically initiated-explosively actuated line cutter.

The secondary reference, Kenzie, discloses a device for severing a reefing line. The de-reefing cutter 22 includes a knife barrel 26. (Col. 2, line 19-21.) The knife barrel 26 has a bore 44 to receive the reefing line 20. (Col. 2, lines 34-37.) A knife 48 is slidably mounted in a slot 42 and is held in a fixed location to one side of the bore 44 by a shear pin 50 passing through the knife. (Col. 2, lines 38-40.) A piston assembly 56 is provided to drive the knife 48. (Col. 2, lines 44-46.) The piston assembly 56 includes a piston 58 and a spring 60. (Col. 2, lines 44-46.) The piston assembly 56 is held against axial movement by a number of balls 80 in a bore 78 extending diametrically through a retainer 66. (Col. 3, lines 54-59.) A release pin 82 is slidably received in the retainer 66 and has a groove 88 formed in

its outer surface to permit the balls 80 to move out of the groove 76 when the groove 88 is aligned with the bore 78. (Col.2, lines 60-68.) In operation, a timing mechanism 112 causes the release pin 82 to move to align the groove 88 with the bore 78 so that the balls 80 move out of the groove 76, permitting the piston assembly 56 to be moved by the spring 60 toward and into contact with the head 54 of the knife 48. The pressure of the piston assembly on the head of the knife causes the shear pin 50 to break. The piston assembly then drives the knife 48 through the reefing line 20. (Col.4, lines 26-38.)

That is to say, as far as base claim 1 is concerned, for example, the recited element of a spring-biased line cutter is not shown. Kenzie has no spring that biases his knife 48 toward anything. His knife 48 is simply held in a fixed location by a shear pin 50 passing through the knife. The recited element of means for mechanically restricting a spring-biased line cutter from engaging and severing the extraction line is not shown. Kenzie has no knife restricting means -- Kenzie's shear pin 50 does not restrict the knife 48 from engaging and severing the line. It only holds the knife 48 in a fixed location. The knife 48 is not biased towards the line. The recited element of means responsive to a radio signal from a transmitter on the aircraft for disabling the restricting means so that the cutter is released and severs the extraction line is not shown. Kenzie has no knife restricting means. Therefore, it has no means for disabling one, and certainly no radio-signal responsive means for disabling one.

It is the Examiner's further position that <u>Tillman</u> shows that a radio control means to control a distant actuator is well known and that it would have been obvious to have made the whole system remotely controlled.

Since the Examiner has not identified either a knife restricting means or a means for disabling it in Kenzie, even if Tillman showed that a radio control means to control a distant actuator was well known, it is still not clear how Kenzie could be in modified in view of Tillman to obtain Applicant's claimed invention.

Therefore, the additional citation of Tillman still fails to remedy Underwood's deficiencies.

MPEP 2143 (Basic Requirements of a Prima Facie Case of Obviousness) requires that to establish a prima facie case of obviousness, the prior art references, when combined, must teach all the claim limitations. The Examiner has not met this basic criterion since the secondary and the tertiary reference fail to remedy the deficiencies of the primary reference.

MPEP 2143 (Basic Requirements of a Prima Facie Case of Obviousness) additionally requires that to establish a prima facie case of obviousness, there must be a suggestion to combine reference teachings. This criterion has not even been addressed by the Examiner.

His justification for combining <u>Kenzie</u> with <u>Underwood</u> is that "it would have been obvious as a substitution of parts." He is simply saying that one could substitute elements from <u>Kenzie</u> in <u>Underwood</u>. He does not explain why one of ordinary skill in the art would have made the substitution in the first place. There is no suggestion to make the combination in the references. The suggested combination of references would require a substantial reconstruction and redesign of the elements shown in <u>Underwood</u> as well as a change in the basic principle under which the <u>Underwood</u> construction was designed to operate. <u>Underwood</u> teaches explosive actuation of his cutter, whereas the claimed invention requires no explosives. This is a hindsight reconstruction of Appellants' invention.

Compare In re Ratti, 123 USPQ 349, 352 (CCPA 1959).

His justification for modifying the foregoing proposed combination of references with <u>Tillman</u> is that the modification is well known and thus obvious. The CCPA and the CAFC have rejected this argument. Legal conclusions as to obviousness cannot be based on such general observations. They must be based on all of the facts of record. *See In re Wagner*, 152 USPQ 552, 558 (CCPA 1967)(rejecting the decision of the Board that "the modification of a compound by the addition of one or more methyl groups is well known and thus obvious").

It is respectfully submitted that the rejection of claims 1 and 6-13 under 35 U.S.C. §103 is based upon hindsight using the teachings of appellants' own disclosure and finds no basis in the prior art cited against this application.

7. Summary

For the foregoing reasons, it is submitted that the Examiner's rejection of claims 1 and 6-13 was erroneous, and reversal of his decision is respectfully requested.

Respectfully submitted,

Mark N. Heflin James B. Stewart Samuel L. Kaesemeyer

ALAN P. KLEIN Attorney for Applicants

Phone: (703) 696-8113

Appendix

Claim 1 (previously presented): A device for severing an extraction line connected between a cargo load and an extraction parachute when the cargo load fails to eject from an aircraft, the device comprising:

a cutter spaced from and spring-biased in the direction of the extraction line; a housing for the cutter;

means for mechanically restricting the cutter from engaging and severing the extraction line; and

means responsive to a radio signal from a transmitter on the aircraft for disabling the restricting means so that the cutter is released and severs the extraction line.

Claim 2 (currently amended): A device for severing an extraction line connected between a cargo load and an extraction parachute when the cargo load fails to eject from an aircraft, the device comprising:

a cutter spaced from and spring-biased in the direction of the extraction line; a housing for the cutter;

means for mechanically restricting the cutter from engaging and severing the extraction line; and

means responsive to a radio signal from a transmitter on the aircraft for disabling the restricting means so that the cutter is released and severs the extraction line.

wherein the restricting means includes a pivotable trip lever positioned in the way of the cutter.

Claim 3 (previously presented): The device recited in claim 2 wherein the disabling means includes:

an activatable solenoid connected to the trip lever for pivoting the trip lever out of the way of the cutter.

Claim 4 (previously presented): The device recited in claim 3 wherein the disabling means includes:

a radio receiver in circuit with the solenoid and responsive to the radio signal for activating the solenoid.

Claim 5 (previously presented): The device recited in claim 4 wherein the disabling means includes:

a battery in circuit with the solenoid for powering the solenoid.

Claim 6 (previously presented): The device recited in claim 1 wherein the housing includes an upper plate and a lower plate, the lower plate being machined to form pockets for the cutter, restricting means and disabling means to be mounted in.

Claim 7 (previously presented): The device recited in claim 6 wherein the upper plate is machined to form mounting and guiding slots for the cutter.

Claim 8 (previously presented): The device recited in claim 7 wherein the housing includes a pair of identical outer plates having a plurality of weight-reducing holes.

Claim 9 (previously presented): The device recited in claim 8 wherein the housing

includes a plurality of spacers for spacing the upper and lower plates.

Claim 10 (previously presented): The device recited in claim 9 wherein the housing includes means for clamping the outer plates and the spaced apart upper and lower plates together.

Claim 11 (previously presented): The device recited in claim 10 wherein the clamping means includes a plurality of bolts and nuts, the bolts passing through the spacers and the plates.

Claim 12 (previously presented): The device recited in claim 11 wherein the upper and lower plates are made from aluminum.

Claim 13 (previously presented): The device recited in claim 1 in combination with an extraction line connected between an extraction parachute and a cargo load.

Claim 14 (previously presented): A device for severing an extraction line connected between a cargo load and an extraction parachute when the cargo load fails to eject from an aircraft, the device comprising:

a cutter spaced from and spring-biased in the direction of the extraction line;
a pivotable trip lever positioned in the way of the cutter for mechanically
restricting the cutter from engaging and severing the extraction line;

an activatable solenoid connected to the trip lever for pivoting the trip lever out of the way of the cutter so that the cutter is released and severs the extraction line;

a radio receiver in circuit with the solenoid and responsive to a radio signal from a transmitter on the aircraft for activating the solenoid;

a battery in circuit with the solenoid for powering the solenoid;

an aluminum upper plate and an aluminum lower plate, the lower plate being machined to form pockets for the cutter, restricting means and disabling means to be mounted in, and the upper plate being machined to form mounting and guiding slots for the cutter;

a pair of identical outer steel plates having a plurality of weight-reducing holes;

a plurality of spacers for spacing the upper and lower plates; and

a plurality of bolts and nuts for clamping the outer plates and the spaced apart upper and lower plates together, the bolts passing through the spacers and the plates.

Claim 15 (previously presented): The device recited in claim 14 in combination with an extraction line connected between an extraction parachute and a cargo load.

Claim 16 (withdrawn): A method of severing an extraction line connected between an extraction parachute and a cargo load when the cargo load fails to eject from an aircraft, the method comprising the steps of:

spacing a cutter from the extraction line;

spring-biasing the cutter in the direction of the extraction line;

mechanically restricting the cutter with restricting means from engaging and severing the extraction line; and

disabling the restricting means in response to a radio signal from a transmitter on the aircraft so that the cutter is released and severs the extraction line.

Claim 17 (withdrawn: The method recited in claim 16 wherein the restricting step includes:

positioning a pivotable trip lever in the way of the cutter.

Claim 18 (withdrawn): The method recited in claim 17 wherein the disabling step includes:

transmitting a radio signal from a transmitter on the aircraft.

Claim 19 (withdrawn): The method recited in claim 18 wherein the disabling step includes:

pivoting the trip lever out of the way of the cutter.

Claim 20 (withdrawn): The method recited in claim 19 wherein the disabling step includes:

activating a solenoid connected to the trip lever.